

		Stander Intensity 36 FX600E	Stander Intensity 42 FX600E
GENERAL	SKU	WSTN36SFX600E1 B	WSTN42SFX600E1B
	Category	Stand-On	Stand-On
	Family	Stander Intensity	Stander Intensity
	Class	Heavy-duty	Heavy-duty
	Generation	Gen 1	Gen 1
	MSRP	9820	9920
CONTROLS	Operator Control Type	Quad Lever Ball Bearing	Quad Lever Ball Bearing
	Hour Meter	Digital	Digital
ENGINE	Vendor	Kawasaki	Kawasaki
	Model	FX600E	FX600E
	Start Type	Electric	Electric
	Horsepower	19 HP	19 HP
PRODUCTIVITY	Forward Speed	8.2 MPH	8.2 MPH
	Reverse Speed	3.5 MPH	3.5 MPH
	Fuel Capacity	5.5 GAL	5.5 GAL
	Max Acres Per Hour	3.02	3.52
DRIVE SYSTEM	Type	Hydro	Hydro
	Motor	Danfoss 12 cu in	Danfoss 12 cu in
	Pump	Hydro-Gear 10 cc	Hydro-Gear 10 cc
	Transaxle	NA	NA
	Transmission	NA	NA
DECK	Deck Size	36 IN	42 IN
	Deck Type	Floating-side discharge	Floating-side discharge
	Configuration	Aero Core	Aero Core
	Lift System	Quick-Cut	Quick-Cut
	Blade Quantity	2	2
	Blade Length	18 IN	21 IN
	Deck Min. Cut Height	1 IN	1 IN
	Deck Max. Cut Height	5 IN	5 IN
	Steel Gauge	7 Gauge	7 Gauge
	Spindle Type	Ductile Iron	Ductile Iron
DIMENSIONS	Weight	717 LB	740 LB
	Length	62.00 IN	70.00 IN
	Width w/ Deflector Down	49.50 IN	55.00 IN
	Width w/ Deflector Up	36.50 IN	42.50 IN
CASTER WHEELS	Rim Diameter	5.00 IN	5.00 IN
	Tire Diameter	11.00 IN	11.00 IN
	Tire Width	4.00 IN	4.00 IN
REAR WHEELS	Rim Diameter	10.00 IN	10.00 IN
	Tire Diameter	18.00 IN	18.00 IN
	Tire Width	8.50 IN	8.50 IN
		Stander Intensity 36 FX600E	Stander Intensity 42 FX600E

LOVE YOUR LAND

STIHL SHOP CHRISTCHURCH